



# ARCHITECT BASE



## Latex primer paint for interiors

### APPLICATION

ARCHITECT BASE is designed to make primer paint coats on cement, cement-lime, gypsum, plasterboard surfaces as well as on glass fiber wallpapers. After dyeing with one of the 8 available colors, it is used as a base for dark and bright paint colors or for repainting dark colors into light ones.

### PROPERTIES

ARCHITECT BASE is an ecological primer that levels the absorbency of the surface and improves the adhesion of the subsequent paint coatings. It improves the adhesion of topcoat paints, increasing their efficiency. It stabilizes the surface and increases the durability of the coating. It can be dyed into 8 colors available in the base.

### SUBSTRATE PREPARATION

The surface must be dry, clean and free from dust and grease. Glossy surfaces must be matted before painting. Repair/fill in all defects and imperfections of the surface and prime them before painting. Remove old, peeling, flaking paint and then prime it with a deep penetrating agent **FAST GRUNT G**. Nicotine, oil, and run-off stains should be covered with **FAST ISOPRO**. Prime fresh plasters, coats and plasterboards with **FAST GRUNT U**. Other raw, absorbent surfaces also need to be primed in advance.

### PREPARATION AND USE

#### PAINTING:

Mix the contents of the package to ensure the uniformity of the product. Do not thin with water. Do not add lime and do not mix with other paints or primers. Purchase the right amount of product to be able to completely execute the project. Do not paint in conditions of high air humidity. Apply when the ambient temperature and the temperature of the surface to be painted is between +10°C and +25°C. Apply the product using a suitable roller, brush or spray. Paint thoroughly, evenly applying a similar amount of product to a specific area of the wall each time, and finish with a gentle vertical movement in one direction. The drying time of the paint under normal conditions is about 2 hours. Painting with topcoat can start after about 4-6 hours. Ensure proper ventilation of the room during painting and drying of the product.

#### CAUTION

Due to the presence of larger granulation fillers in the paint, only the pneumatic spray method should be used for mechanical application.

#### AFTER PAINTING:

Remove as much paint as possible from the painting tools (roller, brush) before proceeding. Wipe up spilled paint immediately with a damp cloth.

### TECHNICAL DATA

Base unit	liter
Base	polymer dispersion with addition of mineral fillers with pigments
Density	about 1.4 kg/m <sup>3</sup>
Drying time of the first layer	about 2 hours
The number of layers	2
Substrate and ambient temperature	from +10 °C to +25 °C

### USE

Depending on the type of substrate, ARCHITECT BASE consumption is about 0.11 / m<sup>2</sup>.



# ARCHITECT BASE



## Latex primer paint for interiors

### PACKAGING

bucket	4.5 l
bucket	10 l

### NORMS

Manufactured in accordance with: PN-EN 13300:2002.

It has a valid hygienic certificate.

VOC content limit (cat. A/a/FW): 30 g/l (2010). The product contains max 1.0 g/l of VOC.

### STORAGE

Store the product in a tightly closed container. Dispose of unused paint properly. Check if there is a collection point for paint waste in your neighborhood. If the amount of paint is left that cannot be reused or stored, do not pour it down the drain. The paint is to be stored and transported in tightly closed, original packaging at temperatures between +5°C and +25°C.

### NOTES / ADDITIONAL COMMENTS

The scope of the product application recommended and specified in the product sheet or the manner of its execution does not release the contractor from carrying out works in accordance with the construction practice and health and safety rules. P.W. FAST guarantees and is responsible for the quality of the product, but has no influence on the method of its application and the conditions in which it was applied.

All the technical data were measured under normal conditions, i.e. temp. +20°C, air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened.

This sheet replaces all previous versions.

### WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water.  
Keep away from children.