



# FAST 1313



## Scrub-resistant latex interior paint

### APPLICATION

**FAST 1313** is a modern latex paint intended for permanent painting of walls and ceilings inside residential premises, including health care facilities, educational institutions and the food industry (without direct contact with food). It is ideal for painting cement, cement-lime and lime plasters, as well as surfaces made of concrete, gypsum, plasterboards, paper wallpapers and fiberglass. Due to its increased covering power and resistance to moisture, it is recommended for painting kitchens, bathrooms, laundry rooms, toilets and rooms with high traffic that require frequent washing, such as passageways, staircases, waiting rooms, classrooms, gyms, etc.

### PROPERTIES

**FAST 1313** is an ecological matt interior paint based on a water dispersion of synthetic resins with the addition of mineral fillers and pigments. It is characterised by high resistance to washing and scrubbing. It is very efficient, non-drip, easy to apply and has a high hiding power. Creates a durable, water-resistant coating with high adhesion to the surface. It has a limited vapor permeability of the coating. Available in a wide range of colors by **FAST COLOR SYSTEM**.

### SUBSTRATE PREPARATION

Paint **FAST 1313** must be applied to smooth, clean, dry, dust and grease-free surfaces. Remove unstable surface layers and repair any defects. In the case of new plasters, the surface should be primed before painting with **FAST GRUNT U** or with **FAST GRUNT F**. Wash old plasters with water and detergent, let them dry, and then paint. Crumbling surfaces must be washed with water and primed with **FAST GRUNT G** and painted with **FAST 1313** paint. Clean concrete surfaces from dust and loose cement dust with a brush, and then cover with paint. The paint can be used on the following surfaces:

- cement and cement-lime plasters (after a minimum of 28 days from the date of implementation and humidity not higher than 4%) primed with **FAST GRUNT U** or **FAST GRUNT F**.
- concrete (after more than 28 days from execution and with humidity not higher than 4%) primed with **FAST GRUNT U** or **FAST GRUNT F**
- gypsum surfaces (humidity below 1%) primed with **FAST GRUNT U** or **FAST GRUNT F**

LATEX PAINT  
LAST ACTUALISATION: 2022-11-28



# FAST 1313



## Scrub-resistant latex interior paint

### PREPARATION AND USE

Before use, the paint must be thoroughly mixed. **FAST 1313** can be applied with a roller, brush or spray. For painting the first layer, the paint can be thinned to 2% with water, and the second layer should be painted with unthinned paint. The drying time of one coat of paint under normal conditions is about 2 hours. The second painting can be done after about 4-6 hours. The ambient temperature during the works and during drying should be between + 5 °C and + 25 °C.

Additional application guidelines:

- before application, check if the color is as ordered. Any complaints regarding the color will not be considered after the application of the product.
- in order to avoid differences in shades on one architectural surface, works should be carried out without interruptions, using packages with paint of the same production batch, previously mixed with each other in a large caster.
- follow the general technique of painting with wall paints.

### CAUTION

In the case of using paints with very intense colors, due to their reduced coverage ability, the use of FAST GRUNT F base paint is required in a shade similar to the color of the paint.

Parameters of airless spray based on the WAGNER - ProSpray 3.23 device

- nozzle diameter 517-519
- pressure 190-220
- bar mesh filter 50
- thinning max. up to 2% with the first layer

### Instructions for the use of the paint coating

The paint coating acquires its full functional properties (scrub resistance/washability) after complete hardening, i.e. after 28 days from the end of painting.

Cleaning of surfaces finished with a coating of latex paint should be carried out with a cloth, sponge or soft brush soaked in water or with an alcohol-free detergent, e.g. dishwashing liquid or soap. This method removes stains from the paint without the risk of their shining or abrasion of the coating.

To remove dirt, agents containing chlorine or bleaches should not be used as they may discolor pigments contained in the paint.

During washing, avoid excessive force and prolonged friction as they may damage the coating.

### TECHNICAL DATA

Base unit	liter
Base	synthetic copolymers z addition of fillers and pigments
Density	about 1.5 kg/m <sup>3</sup>
Drying time of the first layer	about 2-4 hours
Usage	after min. 24 hours
Substrate and ambient temperature	from 5 °C to 25 °C
Wet scrub resistance	Class 2 (PN-EN 13300)

### USE

Depending on the type of substrate, FAST 1313 consumption is from 0.6 to 0.12 l / m<sup>2</sup>. Consumption applies to one layer

LATEX PAINT  
LAST ACTUALISATION: 2022-11-28



# FAST 1313



## Scrub-resistant latex interior paint

### PACKAGING

bucket	2.5 l
bucket	4 l
bucket	10 l

### NORMS

Manufactured in accordance with: PN-C-81914:2002 and PN-EN 13300:2002.

It has a valid hygienic certificate.

VOC content limit (cat. A/a/FW): 30g/l (2010). The product contains max 16.2 g/l of VOC.

### STORAGE

The paint is to be stored and transported in tightly closed, original packaging at temperatures between +5°C and +25°C.

### NOTES / ADDITIONAL COMMENTS

The scope of the product application recommended and specified in the product sheet or the manner of its execution does not release the contractor from carrying out works in accordance with the construction practice and health and safety rules. P.W. FAST guarantees and is responsible for the quality of the product, but has no influence on the method of its application and the conditions in which it was applied.

All the technical data were measured under normal conditions, i.e. temp. +20°C and air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened.

This sheet replaces all previous versions.

### WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water.

Keep away from children.