



# FAST ANTYREFLEX



## Indoor latex paint

### APPLICATION

FAST ANTYREFLEX is intended for painting of walls and ceilings inside residential premises, including health care facilities, educational institutions and the food industry (without direct contact with food). It can be used on cement, cement-lime, gypsum, concrete surfaces, mineral plasters, plasterboards, as well as paper and fiberglass wallpapers.

### PROPERTIES

High-quality ecological latex paint with high covering properties, characterized by its snow whiteness. It creates a deep matt, anti-reflective coatings, eliminating any surface imperfections such as bulges, unevenness, roller marks, streaks, etc. As a result, the walls painted with FAST ANTYREFLEX paint give the impression of perfect smoothness and flawless appearance.

The paint is not intended for tinting.

### SUBSTRATE PREPARATION

The surface must be clean, dry, free of grease and dust. Scratches and deficiencies must be repaired and filled. The paint should be applied on strong, compact surfaces. The surfaces to be painted should be thoroughly dusted and then washed with water. Walls painted with chalk and loose surfaces should be washed off and then primed with FAST GRUNT G deeply penetrating concentrate. Drywall and absorbent surfaces based on gypsum or dolomite must be primed with FAST GRUNT U.

The paint can be used on the following surfaces:

- cement and cement-lime plasters (after minimum 28 days from the date of application and humidity not higher than 4%) primed with FAST GRUNT G or FAST GRUNT U.
- concrete (after more than 28 days from application and with humidity not higher than 4%) primed with FAST GRUNT G or FAST GRUNT U
- gypsum surfaces (humidity below 1%) primed with FAST GRUNT G or FAST GRUNT U

### PREPARATION AND USE

Before use, mix the contents of the package thoroughly. The paint should be applied in two layers, with a roller, spray or possibly with a brush. The ambient temperature during the works and during drying should be between +5°C and +25°C. Drying time approximately 2 hours. It is recommended to apply the next layers after at least 4 hours. Follow the general technique of painting with wall paints.

Parameters of airless spray based on the WAGNER - ProSpray 3.23 device

- nozzle diameter 517-519
- pressure 190-220
- bar mesh filter 50
- thinning max. up to 2%

### CAUTION

The paint coating acquires its full functional properties (scrub resistance/washability) after complete hardening, i.e. after 28 days from the end of painting.

LAST ACTUALISATION: 2022-11-28



# FAST ANTYREFLEX



## Indoor latex paint

### TECHNICAL DATA

Base unit	liter
Base	synthetic copolymers z addition of fillers and pigments
Density	about 1.5 kg/m <sup>3</sup>
Drying time of the first layer	about 2-4 hours
The number of layers	2
Substrate and ambient temperature	from +5 °C to +25 °C
Wet scrub resistance	class 3 (PN-EN 13300)

### USE

Depending on the type of substrate, FAST ANTYREFLEX consumption is from 0.6 to 0.12 l / m<sup>2</sup>.  
Consumption applies to one layer

### NORMS

Manufactured in accordance with: PN-C-81914:2002 and PN-EN 13300:2002

It has a valid hygienic certificate.

VOC content limit (cat. A/a/FW): 30g/l (2010). The product contains max 15.6 g/l of VOC.

### STORAGE

The paint is to be stored and transported in tightly closed, original packaging at temperatures between +5°C and +25°C.

### NOTES / ADDITIONAL COMMENTS

The scope of the product application recommended and specified in the product sheet or the manner of its execution does not release the contractor from carrying out works in accordance with the construction practice and health and safety rules. P.W. FAST guarantees and is responsible for the quality of the product, but has no influence on the method of its application and the conditions in which it was applied.

All the technical data were measured under normal conditions, i.e. temp. +20°C and air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened.

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water. Keep away from children.

This sheet replaces all previous versions.

### WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water. Keep away from children.

LAST ACTUALISATION: 2022-11-28