



FAST IMPREGO



Silicone impregnating agent

APPLICATION

FAST IMPREGO is intended for impregnation of absorptive surfaces of building elements, such as: stone, brick, plaster traditional, as well as mineral plasters and plasters imitating architectural concrete and travertine. It is ideal for cement, cement-lime, gypsum surfaces, stone, concrete and terrazzo cladding as well as decorative gypsum elements, mineral paint coatings, walls made of ceramic, clinker and silicate bricks, ceramic and cement tiles, cement-fiber boards, etc.

PROPERTIES

FAST IMPREGO high-quality water-based impregnating agent based on silicone dispersion, for impregnating absorbent construction surfaces. After drying, it creates a vapor-permeable zone on the surface of the material that reduces water absorption and protects against frost damage and damage caused by salt crystallization. As a result, the material is better protected against dirt and the development of biological aggression.

SUBSTRATE PREPARATION

The surface must be properly seasoned, clean, dry, free from grease, soot, grease, dust and any impurities that would reduce adhesion. Scratches and defects must be repaired and filled.

PREPARATION AND USE

FAST IMPREGO can be applied with a brush, roller or airless spray, in two layers, the second layer is to be applied after initial drying of the first, i.e. after min. 2 hours.

Works should be carried out at the temperature from +5°C to +25°C, avoiding strong wind and excessive sunlight. Elements and surfaces not intended for impregnation should be carefully covered. Any impregnation stains should be washed off with water as soon as possible. Freshly impregnated surfaces must be protected against rainfall until they are dry, i.e. for a period of at least 4 hours. The time to obtain full protection against water is 7 days from impregnation.

TECHNICAL DATA

Base unit	liter
Base	aqueous dispersion of silicone polymer
Density	about 1,0 kg/m ³
Drying time of the first layer	about 2 hours
The number of layers	1-2
Substrate and ambient temperature	from +5 °C to +25 °C

USE

Depending on the type of substrate, FAST IMPREGO consumption is from 0.1 to 0.2 l / m².

PACKAGING

FAST IMPREGO	2 l
FAST IMPREGO	5 l

NORMS

STORAGE

The product should be stored and transported in tightly closed packaging at temperatures between +5°C and +25°C. The expiry date on the package.

LAST ACTUALISATION: 2022-11-28



FAST IMPREGO



Silicone impregnating agent

NOTES / ADDITIONAL COMMENTS

P.W. FAST guarantees and is responsible for the quality of the product, but has no influence on the method of its application and the conditions in which it was applied. All the technical data were measured under normal conditions, i.e. temp. +20°C and air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened.
This sheet replaces all previous versions.

WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water. Keep away from children.

LAST ACTUALISATION: 2022-11-28