



FAST F-AW Extra Biala



dispersion paint - for indoor use

APPLICATION

FAST F-AW EXTRA BIALA is latex paint intended for painting walls and ceilings inside residential premises, including health care facilities, educational institutions and the food industry (without direct contact with food). It can be used on cement, cement-lime, gypsum, concrete surfaces, mineral and dispersion plasters, plasterboards, as well as paper and fiberglass wallpapers.

PROPERTIES

FAST F-AW EXTRA BIALA is an ecological paint produced on the basis of synthetic copolymers with the addition of fillers minerals and pigments. It has excellent covering properties and is resistant to washing. Coating made with paint FAST F-AW EXTRA BIALA is vapour permeable and low odor. Thanks to its properties, it provides rooms with pleasant microclimate. FAST F-AW EXTRA BIALA is snow-white and perfect for painting ceilings and walls.

SUBSTRATE PREPARATION

The surface must be clean, dry, free of grease and dust. Scratches and defects must be repaired and filled. The paint should be applied on strong, compact surfaces. The surfaces to be painted should be thoroughly dusted and then washed with water. Walls painted with chalk and loose surfaces should be washed and then primed with FAST GRUNT G deeply penetrating concentrate. Drywall and absorbent surfaces based on gypsum or dolomite must be primed with FAST GRUNT U. The paint can be used on the following surfaces:

- cement and cement-lime plasters (after a minimum of 28 days from the date of application and humidity not higher than 4%) primed with FAST GRUNT G or FAST GRUNT U
- concrete (after more than 28 days from execution and with humidity not higher than 4%) primed with FAST GRUNT G or FAST GRUNT U
- gypsum surfaces (humidity below 1%) primed with FAST GRUNT G or FAST GRUNT U

PREPARATION AND USE

Before use, mix the contents of the package thoroughly. The paint should be applied in two layers, with a roller, spray or possibly with a brush. The ambient temperature during the works and during drying should be between +5°C and +25°C. Drying time approximately 2 hours. It is recommended to apply the next layers after at least 4 hours. Follow the general technique of painting with wall paints.

Parameters of airless spray based on the WAGNER - ProSpray 3.23 device

- nozzle diameter 517-519
- pressure 190-220
- bar mesh filter 50
- thinning max. up to 2% with the first layer

CAUTION

The paint coating acquires its full functional properties (scrub resistance/washability) after complete hardening, i.e. after 28 days from the end of painting.

TECHNICAL DATA

Base unit	liter
Base	synthetic copolymers with addition of fillers and pigments
Density	about 1,5 kg/m ³
Drying time of the first layer	about 2-4 hours
Usage	after min. 24 hours
Substrate and ambient temperature	from 5 °C to 25 °C
Wet scrub resistance	Class 3 (PN-EN 13300)

LATEX PAINT
LAST ACTUALISATION: 2022-11-28



FAST F-AW Extra Biala



dispersion paint - for indoor use

USE

Depending on the type of substrate, Fast F-AW Extra Biala consumption is from 0.06 to 0.12 l / m². Consumption applies to one layer

PACKAGING

bucket	4 l
bucket	10 l

NORMS

Manufactured in accordance with: PN-C-81914:2002 and PN-EN 13300:2002 It has a valid hygienic certificate

VOC content limit (cat. A/a/FW): 30g/l (2010). The product contains max 15.6 g/l of VOC.

STORAGE

The paint is to be stored and transported in tightly closed, original packaging at temperatures between +5°C and +25°C.

NOTES / ADDITIONAL COMMENTS

The scope of the product application recommended and specified in the product sheet or the manner of its execution does not release the contractor from carrying out works in accordance with the construction practice and health and safety rules. P.W. FAST guarantees and is responsible for the quality of the product, but has no influence on the method of its application and the conditions in which it was applied. All the technical data were measured under normal conditions, i.e. temp. +20°C and air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened.

WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water.
Keep away from children.

This sheet replaces all previous versions.