



FAST Grunt F



Acrylic primer paint.

APPLICATION

FAST GRUNT F is an acrylic primer paint intended for making primer paint coats on cement, cement-lime, gypsum, plasterboard surfaces as well as on fiberglass wallpapers inside and outside rooms. It is ideal as a primer for dark, intense paint colors and for recoating dark surfaces with light ones.

PROPERTIES

FAST GRUNT F is an environment-friendly primer that levels the absorbency of the surface and improves the adhesion of the subsequent paint coatings. It has good covering and filling properties, increasing the efficiency of topcoats. It has a mild fragrance and high efficiency. It can be pastel colored according to the FAST color palette

SUBSTRATE PREPARATION

The surface must be clean, dry, free of grease and dust. Scratches and defects must be repaired and filled. The paint should be applied on strong, compact surfaces. The surfaces to be painted should be thoroughly dusted and then washed with water. Walls painted with chalk and crumbling surfaces should be washed off and then primed with a deeply penetrating FAST GRUNT G concentrate.

The paint can be used on the following surfaces:

- cement and cement-lime plasters (after a minimum of 28 days from the date of application and humidity not higher than 4%)
- concrete (after more than 28 days after application and humidity not higher than 4%)
- gypsum surfaces (after more than 14 days after application and humidity below 1%)

PREPARATION AND USE

Before use, the paint must be thoroughly mixed. FAST GRUNT F can be applied with a roller, brush or spray. It is permissible to thin the paint with water up to a maximum of 5%. The drying time under normal conditions is approximately 2 hours. Painting with topcoat can start after about 4-6 hours. The ambient temperature during the works and drying should be between +5°C and +25°C.

CAUTION

Due to the presence of larger granulation fillers in the paint, only the pneumatic spray method should be used for mechanical application.

TECHNICAL DATA

Base unit	liter
Base	synthetic dispersion with added fillers and pigments
Density	about 1,4 kg/m ³
Drying time	from 2 hours

USE

Depending on the type of substrate, Fast Grunt F consumption is from 0.1 to 0.14 l / m².

PACKAGING

bucket	4 l
bucket	10 l

NORMS

Manufactured in accordance with PN-EN 1062-1:2005.

It has a valid hygienic certificate.

The limit value of the maximum VOC content for the product: cat. A/a FW:30 g/l.

The content in the product ready for use maximum: 11.5 g/l.

ACRYLIC PAINT
LAST ACTUALISATION: 2022-11-28



FAST Grunt F



Acrylic primer paint.

STORAGE

Store in tightly closed containers at temperatures between +5°C and +25°C. Protect against freezing and overheating.

NOTES / ADDITIONAL COMMENTS

The scope of the product application recommended and specified in the product sheet or the manner of its execution does not release the contractor from carrying out works in accordance with the construction practice and health and safety rules.

P.W. FAST guarantees and is responsible for the quality of the product, but has no influence on the method of its application and the conditions in which it was applied. All the technical data were measured under normal conditions, i.e. temp. +20°C and air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened.

This sheet replaces all previous versions.

WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water.

Keep away from children.

ACRYLIC PAINT
LAST ACTUALISATION: 2022-11-28