



FAST Kwarc S



silicate structural paint of the "Kwartscoat" type (interior and exterior use)

APPLICATION

FAST QUARTZ S is a silicate structural paint intended for performing decorative layers on cement plasters, cement-lime, as well as on surface made of concrete, brick, plaster, plasterboard and asbestos-cement panels as well as mineral wool inside and outside buildings.

PROPERTIES

FAST KWARC S it is a well-covering, silicate textured paint with fine quartz grain, durable and impact-resistant. Easy to apply, it corrects minor irregularities creating a perfectly hardened coating. It is vapour permeable and hydrophobic. Wide color selection from the rich palette of **FAST COLOR SYSTEM**.

SUBSTRATE PREPARATION

FAST KWARC S should be applied to strong, clean, dry, compact, grease and dust free surfaces. Visible scratches and defects must first be repaired and filled. **FAST GRUNT G** deeply penetrating primer should be applied to absorbent, shedding and dusty surfaces. The paint can be used on the following surfaces:

- cement and cement-lime plasters (after a minimum of 28 days from the date of application and humidity not higher than 4%) primed with **FAST GRUNT G** or **FAST GRUNT U**.
- concrete (after more than 28 days from execution and with humidity not higher than 4%) primed with **FAST GRUNT G** or **FAST GRUNT U**
- gypsum surfaces (humidity below 1%) primed with **FAST GRUNT G** or **FAST GRUNT U**

PREPARATION AND USE

Mix thoroughly before use. Apply the undiluted layer of paint with a facade brush, mini block paintbrush, textured roller or trowel. Apply the final pattern using a suitable roll or other tool. The product can also be applied by means of pneumatic spraying with devices such as **WAGNER PC 35** or **Euromair DECOPRO 120**. **FAST KWARC S** should be applied at air and surface temperature from +5°C to +25°C. Do not apply under heavy rain wind and full sun conditions. The drying time is about 4-6 hours. It is recommended to apply the subsequent layers after at least 2 hours. Additional application guidelines:

- In order to avoid differences in shades on one architectural surface, works should be carried out without interruptions, using packages with paint of the same production batch, previously mixed with each other in a large caster.
- Protect the paint from unfavorable atmospheric phenomena until it is completely dry by means of protective covers mounted on scaffolding.
- Follow the general rules of painting with facade paints.

TECHNICAL DATA

Base unit	kg
Base	potassium water glass and acrylic-styrene dispersion with the addition of fillers
Density	about 1,75 kg/m ³
Open time of work	about 20 min
Drying time	from 4 hours to 6 hours
Drying time of the first layer	about 2 hours
Substrate and ambient temperature	from 5 °C to 25 °C

USE

Depending on the type of substrate, **Fast Kwarc S** consumption is from 1 to 1.4 kg / m². The consumption figures are for one layer.

STRUCTURAL PAINT
LAST ACTUALISATION: 2022-11-28



FAST Kwarc S



silicate structural paint of the "Kwartscoat" type (interior and exterior use)

PACKAGING

bucket 15 kg

NORMS

Manufactured in accordance with: PN-EN 1062-1

STORAGE

The paint is to be stored and transported in tightly closed, original packaging at temperatures between +5°C and +25°C. Shelf life is 24 months.

NOTES / ADDITIONAL COMMENTS

The scope of the product application recommended and specified in the product sheet or the manner of its execution does not release the contractor from carrying out works in accordance with good construction practice and health and safety rules. P.W. FAST guarantees and is responsible for the quality of the product, but exerts no influence on the method of its application and the conditions in which it was applied. All the technical data were measured under normal conditions, i.e. temp. +20°C and air humidity 60%. Under conditions other than the above, the drying time may change, i.e. it may be extended or shortened. This sheet replaces all its previous versions.

WARNING

While working, avoid direct contact with the skin and protect the eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. Rinse soiled skin immediately with plenty of water. Keep away from children.

STRUCTURAL PAINT
LAST ACTUALISATION: 2022-11-28